

Frequently Asked Questions

Q: What is the stud opening required for an EzyJamb?

For EzyJamb Classic Adjust - EZC, ensure that the stud opening is square and level, measuring:

- Single door width +15mm maximum
- Double door width + 18mm maximum
- Door height +8mm at header and + 25mm at floor level (depending on floor clearance. Check with the project manager on site to confirm floor coverings).

Important: Studco strongly recommends a timber stud or a 0.75 BMT metal stud on both sides of the opening.

For EzyJamb Single Rebate - SRC openings, please contact the EZ Concept team on 1300 399 526.

Q: What's so unique about the EzyJamb flush finish door jamb?

EzyJamb® is the original door jamb system that eliminates trim, giving you that subtle, contemporary, clean line look. It's durable, it's affordable and is at home in commercial offices and showrooms, quality homes and public spaces like hospitals and schools.

Q: How is the EzyJamb constructed?

EzyJamb is a split type architrave-free door jamb system which is fully adjustable to any wall thickness.

Q: How is EzyJamb fixed?

EzyJamb is screw fixed to the jamb studs and header with flat headed screws every 200mm (through the perforated sides), into the wall stud and double screwed at the hinge points and top corners.



Q: How does the costs compare to a standard timber door frame?

Ezy Jamb purchase cost may be initially slightly greater, but when installation, labour and architraves for a timber door frame are considered, there is not a significant difference.

Q: Can I match my windows with the clean line look?

Yes, a large range of EzyReveal angles are available so that your whole project will blend in with the architrave free look.

Q: What jamb studs do I use for the opening for a EzyJamb?

The manufacturer strongly recommends a timber stud or a 0.75 BMT metal stud on both sides of the opening.

Q: Are your frames welded?

EzyJamb frames are not welded and are clipped together using a unique EzyJamb system that ensures an easy install and smooth finish.

Q: What material are EZ Concept products made from?

EZ Concept products are manufactured from highest quality cold-formed steel sections.

Q: Is EZ Concept an environmentally friendly brand?

Responsibility of and caring for the environment in which we live is a Studco hallmark that is promoted at every level of our business. Our commitment to the environment and ISO14001 accreditation means less waste and no chemical treatment is required on our products.

View Studco's Environmental Policy for more information.

Frequently Asked Questions



Q: How is the architrave-free EzyJamb finished with plaster walls?

EzyJamb is fitted after the plaster lining has been installed, and has 35mm perforated sides for flush finishing with top coat into the walls, achieving clean architrave free lines around the doorway.

Q: Do I have to use any special paint or preparation methods on EZ Concept products?

EZ Concept products are manufactured from zinc annealed steel and meet the finished surfaces standard AS/NZS 2311:2009 to ensure it can be painted immediately, without any special preparation, so long as it is free of dust, dirt and oil.

Q: Can I fit architraves with the EzyJamb system?

Yes, architraves can be fitted, but the EzyJamb concept is designed to create an 'architrave-free' opening.

Q: How can I achieve that flush finish look throughout the rest of my project?

Check out our extensive EzyFinishing range.

Q: What hinges should be used with EzyJamb?

EzyJamb can be used with a variety of concealed and non-mortised hinges. Stainless steel EzyJamb hinges are provided with each door frame (lift off hinges are available if required).

Q: Can EzyJamb be used in a doorway with no header?

Yes, custom made EzyJambs are available with no header for full height doors.

Q: Can EzyJamb be used if I have a solid core door?

Yes, EzyJamb can be used with a solid core door. You will need to make sure that you are using the correct hinge and quantity to accommodate the door weight, making sure the hinge screws penetrate through to the timber stud behind the jamb.

Q: Will plaster crack around the edges of the finished EzyJamb?

Plaster around the edges of the EzyJamb will not crack if the EzyJamb is installed according to the installation guide — i.e. must be screwed off every 200mm and double screwed at the hinge points and top corners. EzyJamb then becomes an integral part of the wall.

Q: How long does it take to fit an EzyJamb frame?

10 -15 minutes depending on the installer.

Q: Can EzyJamb be used with masonry or brick walls?

Yes, masonry wall installation instructions are available. Contact sales@ezconcept.com.au for more details.

Q: What about skirting — what can be used?

Any type of skirting can be used but to complement the flush finish look — "Alubase" slim line aluminium skirting which is only 1.6mm in thickness is the best matching option.

Q: Cavity sliders— how do I match in the clean line look?

A range of CavKit trims are available to transform your existing cavity slider unit into an architrave free door way. We can also supply complete flush finish CavKits. Contact us to find out more about our SlideSet flush finish cavity sliding system.

